

Bayfield® MULTIHEIGHT WALL SYSTEMS



The Bayfield® retaining wall system combines earthen tones, rich textures, varied contours and all the advantages of the rear-lip locator, making it a reliable and easy-to-install alternative to natural stone walls. Use of the 6-inch-high Bayfield units alone or mixed with the 3-inch-high blocks creates stunning retaining walls.

Retaining wall system

- Available in two heights and three face lengths
- Can be used for gravity walls up to 4 feet 6 inches high, including buried course, but excluding the cap*
- Original rear-lip locator
- Taller walls can be built using geosynthetic reinforcement or the Anchorplex™ retaining wall system when designed by a qualified engineer
- Minimum outside radius, measured on the top course to the front of the units: 4 feet**
- Minimum inside radius, measured on the base course to the front of the units: 8 feet**







Freestanding wall system

- Available in two heights and three different face lengths for a random look
- Can be used for straight or curved walls
- Use as seating areas, borders and courtyards
- Can be used for walls up to 3 feet high, including buried course, but excluding the cap
- Columns or pilasters constructed with the pillar units can be built up to 6 feet high, including buried course
- Minimum radius using three units of the same height: 3 feet
 9 inches**
- Maximum straight-wall length between design elements: 10 feet**

^{*}This height assumes cores are filled with drainage aggregate, level backfill and clean, compacted sand or gravel and no surcharge.

^{**}May vary depending on the installation pattern.



No pins. No mortar. No misalignments.

Rear-lip locator, invented by Anchor, makes installation fast and accurate. Anchor™ - the original rear-lip product!





PRODUCT INFORMATION

See anchorwall.com for installation instructions.







6" Retaining Wall Units	Large	Medium	Small	
Approximate Dimensions*	6" x 18" x 10"	6" x 12" x 10"	6" x 6" x 10"	
Approximate Weight*	59 lbs.	43 lbs.	21 lbs.	
Coverage	0.75 sq. ft.	0.50 sq. ft.	0.25 sq. ft.	
Setback/System Batter	1½"/10.6°	1½″/10.6°	11/8"/10.6°	

	AND ASSESSED AND ASSESSED.		16.96	
3" Retaining Wall Units	Large	Medium	Small	
Approximate Dimensions*	3" x 18" x 9 ¹ / ₂ "	3" x 12" x 9 ¹ / ₂ "	3" x 6" x 9 ¹ / ₂ "	
Approximate Weight*	36 lbs.	25 lbs.	12 lbs.	
Coverage	0.38 sq. ft.	0.25 sq. ft.	0.13 sq. ft.	
Setback/System Batter	⁹ / ₁₆ "/10.6°	⁹ / ₁₆ "/10.6°	⁹ / ₁₆ "/10.6°	







6" Freestanding Wall Units	Large	Medium	Small
Approximate Dimensions*	Front, 6" x 18" x 9 Back, 6" x 16" x 9"	6" × 12" × 9" 6" × 10" × 9"	6" x 6" x 9" 6" x 4" x 9"
Approximate Weight*	70 lbs.	45 lbs.	20 lbs.
Coverage	0.71 sq. ft.	0.46 sq. ft.	0.21 sq. ft.







3" Freestanding Wall Units	Large	Medium	Small
Approximate Dimensions*	Front, 3" x 18" x 9 Back, 3" x 16" x 9"	3" × 12" × 9" 3" × 10" × 9"	3" × 6" × 9" 3" × 4" × 9"
Approximate Weight*	35 lbs.	23 lbs.	10 lbs.
Coverage	0.35 sq. ft.	0.23 sq. ft.	0.10 sq. ft.









		N. A.		A STATE OF THE PARTY OF THE PAR	
Acessory Units	XL™ Cap	Step	6" Column	3" Column	
Approximate Dimensions*	Front, 3" x 18" x 13" Back, 3" x 12" x 13"	6" × 16" × 12"	6" x 18" x 9"	3" × 18" × 9"	
Approximate Weight*	44 lbs.	89 lbs.	75 lbs.	38 lbs.	
Coverage	1.25 lin. ft.		1.13 lin. ft.	0.56 sq. ft.	

^{*}Product dimensions are height by face length by depth. Actual dimensions and weights may vary from these approximate values due to variations in manufacturing processes. Specifications may change without notice. See your Anchor representative for details, color options, block dimensions and additional information.

Anchor Wall Systems, Inc., 5959 Baker Road, Suite 390, Minnetonka, MN 55345. A&B1037

72.3340.1 12/11 4015



^{© 2011} Anchor Wall Systems, Inc. (AWS). The "Anchor A" and "Anchor Build Something Beautiful" logos, "Anchorplex", "Bayfield" and "XL" are trademarks of AWS. The wall system blocks are covered by the AWS Limited Warranty. For a complete copy, visit your local dealer or see anchorwall.com.